

## GASOLINE

	TEST		LIMITS	TEST METHOD
1	DENSITY@ 15 C	KG/M3	725MIN/790MAX	ASTM-D-1298
2	DISTILLATION TEMPERATURE			ASTM-D-86
3	10% EVAPORATED	°C	70 MAX	ASTM-D-86
4	50% EVAPORATED	°C	115 MAX	ASTM-D-86
5	90%EVAPORATED	°C	180 MAX	ASTM-D-86
6	FINAL BOILING POINT	°C	204 MAX	ASTM-D-86
7	RESIDUE	VOL.%	2 MAX	ASTM-D-86
8	TOTAL SULPHUR	WT%	0.15 MAX	ASTM-D-1266
9	COPPER CORROSION 3HRS AT 40°C		1 MAX	ASTM-D-130
10	REID VAPOUR PRESSURE	KG/CM3	0.67 MAX	ASTM-D-323
11	INDUCTION PERIOD @100°C	MIN	240 MIN	ASTM-D-525
12	OCTANE NUMBER RESEARCH METHOD		93 MIN	ASTM-D-2699
13	EXISTENT GUM	MG/100 ML	5 MAX	ASTM-D-381
14	COLOUR		NIL	
15	NO LEAD ANTI-KNOCK ADDITIVE			
16	NO DYE			
17	NO ALCOHOL/MTBE OR ETHERS			
18	NO MANGANESE-BASED ANTI-KNOCK			
19	ADDITIVE			
20	NO IRON-BASED ANTI-KNOCK ADDITIVE			